



## 1 L Black Ink type JP-K72

### SECTION 1 - Identification of the substance/mixture and of the company/undertaking

#### 1.1. - Product identifier

Trade name 1 L Black Ink type JP-K72

Chemical name

Product-type Mixture Product code K72

#### 1.2. - Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. - Details of the supplier of the safety data sheet

Southern Technology Limited

61 Nursery Road

Phillipstown

Christchurch

Phone +643 389 9258 Fax +643 389 2162

Website [www.stinks.co.nz](http://www.stinks.co.nz)

#### 1.4. - Emergency telephone number Poisons Information Centre 0800 764 766

### SECTION 2 - Hazards identification

#### 2.1. - Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2	Flammable liquids, Category 2
Eye Irrit. 2	Eye irritation - Category 2
Skin Sens. 1	Skin sensitization - Category 1
STOT SE 3 (H336)	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

#### 2.2. - Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Contains: butanone, ethyl methyl ketone (CAS No.: 78-93-3)

Signal word : Danger

Hazard pictograms



Hazard statements

H225	Highly flammable liquid and vapour
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H412	Harmful to aquatic life with long lasting effects

Precautionary statements



## 1 L Black Ink type JP-K72

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground/bond container and receiving equipment.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust, fume, gas, mist, vapours, spray .
P280	Wear protective gloves, protective clothing, eye protection, face protection .
EUH-phrases	
EUH066	Repeated exposure may cause skin dryness or cracking
EUH208	Contains Resin acids and Rosin acids, fumarated, esters with glycerol (97489-11-7) . May produce an allergic reaction

### 2.3. - Other hazards

## SECTION 3 - Composition/information on ingredients

### 3.1. - Substances

Not applicable

### 3.2. - Mixtures

Chemical name	No	%	Class	Spec. concentrations
butanone, ethyl methyl ketone	CAS No. : 78-93-3 Index No. : 606-002-00-3 EC No. : 201-159-0	70 - 80	Eye Irrit. 2 - H319 Flam. Liq. 2 - H225 STOT SE 3 (H336) - H336	Not applicable
Resin acids and Rosin acids, fumarated, esters with glycerol	CAS No. : 97489-11-7 Index No. : EC No. : 307-051-0	10 - 20	Aquatic Chronic 4 - H413 Eye Irrit. 2 - H319 Skin Sens. 1 - H317	Not applicable
reaction mass of: tert-alkyl(C12-C14)ammonium bis[1-[(2-hydroxy-5-nitrophenyl)azo]-2-naphthalenolato(2-)]-chromate(1-), tert-alkyl(C12-C14)ammonium bis[1-[(2-hydroxy-4-nitrophenyl)azo]-2-naphthalenolato(2-)]-chromate(1-), tert-alkyl(C12-C14)ammonium bis[1-[[5-(1,1-dimethylpropyl)2-hydroxy-3-nitrophenyl]azo]2-naphthalenolato(2-)]-chromate(1-), tert-alkyl(C12-C14)ammonium [[1-[(2-hydroxy-5-nitrophenyl)azo]-2-naphthalenolato(2-)]-[1-[(2-hydroxy-5-nitrophenyl)azo]2-naphthalenolato(2-)]]-chromate(1-), tert-alkyl(C12-C14)ammonium [[1-[[5-(1,1-dimethylpropyl)-2hydroxy-3-nitrophenyl]azo]-2naphthalenolato(2-)]-[1-[(2-hydroxy-5-nitrophenyl)azo]-2-naphthalenolato(2-)]]-chromate(1-), tert-alkyl(C12-C14)ammonium ((1-(4(or 5)-nitro-2-oxidophenylazo)-2-naphthalolato)(1-(3-nitro-2-	CAS No. : 117527-94-3 Index No. : 611-044-00-0 EC No. : 403-720-7	1 - 10	Aquatic Chronic 2 - H411	Not applicable



## 1 L Black Ink type JP-K72

oxido5-pentylphenylazo)-2-naphtho lato))chromate(1-)				
--	--	--	--	--

### SECTION 4 - First aid measures

#### 4.1. - Description of first aid measures

##### Measures in case of inhalation

- Irritating to respiratory system.
- Provide fresh air.
- Get medical advice/attention.

##### Measures in case of contact with skin

- When in doubt or if symptoms are observed, get medical advice.
- Irritating to skin.
- After contact with skin, wash immediately with plenty of water and soap.
- Remove contaminated, saturated clothing immediately.

##### Measures in case of contact with eyes

- Irritating to eyes.
- In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

##### Measures in case of ingestion

- Do NOT induce vomiting.
- Vomiting
- Nausea
- Get medical advice/attention.

#### 4.2. - Most important symptoms and effects, both acute and delayed

##### Symptoms and effects after inhalation

- Irritating to respiratory system.



---

## 1 L Black Ink type JP-K72

---

### Symptoms and effects after contact with skin

- Causes skin irritation.
- Repeated exposure may cause skin dryness or cracking.

### Symptoms and effects after contact with eyes

- Irritating to eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

### Symptoms and effects after ingestion

- The following symptoms may occur: Vomiting
- Nausea

### 4.3. - Indication of any immediate medical attention and special treatment needed

- Treat symptomatically.
- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

---

## SECTION 5 - Firefighting measures

---



---

## 1 L Black Ink type JP-K72

---

### 5.1. - Extinguishing media

Suitable extinguishing media

- Carbon dioxide (CO<sub>2</sub>)
- Dry extinguishing powder

Unsuitable extinguishing media

- High power water jet

### 5.2. - Special hazards arising from the substance or mixture

Special hazards -

- Vapours are heavier than air.
- Vapours can travel considerable distances to a source of ignition where they can ignite, flash back, or explode.

Decomposition products

- Carbon dioxide (CO<sub>2</sub>)
- Carbon monoxide

### 5.3. - Advice for firefighters

- Wear a self-contained breathing apparatus and chemical protective clothing.
- Move undamaged containers from immediate hazard area if it can be done safely.
- In case of fire and/or explosion do not breathe fumes.

---

## SECTION 6 - Accidental release measures

---

### 6.1. - Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

- Use personal protection equipment.
- Provide adequate ventilation.
- Remove all sources of ignition.
  - Evacuate area.

For emergency responders

- No information available.

### 6.2. - Environmental precautions

- Do not allow to enter into surface water or drains.
- Absorb spillage to prevent material damage.

### 6.3. - Methods and material for containment and cleaning up

Appropriate containment techniques

- Soak up inert absorbent and dispose as waste requiring special attention.
  - Collect in closed and suitable containers for disposal.
  - Collect spillage.

Appropriate clean-up procedures

- Wash with plenty of water.

Inappropriate techniques

- No information available.

### 6.4. - Reference to other sections



## 1 L Black Ink type JP-K72

- Disposal: see section 13
- Personal protection equipment: see section 8
- SECTION 6: Accidental release measures

### SECTION 7 - Handling and storage

#### 7.1. - Precautions for safe handling

##### Recommendations

- Avoid: Eye contact
- Avoid: Skin contact
- Provide adequate ventilation.
- Use explosion-proof machinery, apparatus, ventilation facilities, tools etc.
- Keep away from sources of ignition. - No smoking.

##### Advice on general occupational hygiene

- When using do not eat, drink, smoke, sniff.
- Wash contaminated clothing prior to re-use.
- Wash hands before breaks and after work.

#### 7.2. - Conditions for safe storage, including any incompatibilities

- Keep container tightly closed in a cool, well-ventilated place.

#### 7.3. - Specific end use(s)

- Keep away from sources of ignition. - No smoking.
- Handle and open container with care.

### SECTION 8 - Exposure controls/personal protection

#### 8.1. - Control parameters

#### 8.2. - Exposure controls

##### Appropriate engineering controls

- No information available.





## 1 L Black Ink type JP-K72

Individual protection measures, such as personal protective equipment - Suitable eye protection: Eye glasses with side protection

- Protective gloves

- Suitable protective clothing: lab coat

### SECTION 9 - Physical and chemical properties

#### 9.1. - Information on basic physical and chemical properties

<u>Physical state</u>	Liquid	<u>Appearance</u>	Liquid
<u>Color</u>	Black	<u>Odor</u>	characteristic
Odour threshold		No data available	
pH		No data available	
Melting point		-76 °C	
Freezing point		-76 °C	
Boiling point		80 °C	
Flash point		-8 °C	
Evaporation rate		No data available	
flammability		No data available	
Lower explosion limit		1,8 % Vol.	
Upper explosion limit		11,5 % Vol.	
Vapour pressure		10500 Pa	
Vapour density		No data available	
Relative density		0,85	
Density		No data available	
Solubility (Water)		miscible	
Solubility (Ethanol)		No data available	
Solubility (Acetone)		No data available	
Solubility (Organic solvents)		No data available	
Log Kow - Partition coefficient: n-octanol/water		No data available	
Auto-ignition temperature		505 °C	
Decomposition temperature		No data available	
Kinematic viscosity		No data available	



## 1 L Black Ink type JP-K72

Dynamic viscosity	No data available
9.2. - Other information	
VOC content	No data available
Minimum ignition energy	No data available
Conductivity	No data available

### SECTION 10 - Stability and reactivity

#### 10.1. - Reactivity

- This material is considered to be non-reactive under normal use conditions.

#### 10.2. - Chemical stability

- The product is chemically stable under recommended conditions of storage, use and temperature.

#### 10.3. - Possibility of hazardous reactions

- No hazardous reaction when handled and stored according to provisions.

#### 10.4. - Conditions to avoid

- In case of warming: Ignition hazard

#### 10.5. - Incompatible materials

- No information available.

#### 10.6. - Hazardous decomposition products

- No information available.

### SECTION 11 - Toxicological information

#### 11.1. - Information on toxicological effects

Acute toxicity - Not classified

#### Toxicity values of mixture

LD50 oral (rat)	2737 mg/kg
LD50 dermal (rat)	8200 mg/kg
LD50 dermal (rabbit)	6480 mg/kg
LC50 inhalation (rat)	11700 ppmV
LC50 inhalation dusts and mists (rat)	No data available
LC50 inhalation vapours (rat)	No data available

- Based on available data, the classification criteria are not met.

#### Toxicity values of substances

butanone, ethyl methyl ketone  
(78-93-3)

LD50 oral (rat)	2193 mg/kg
LD50 dermal (rabbit)	5000 mg/kg

Skin corrosion/irritation - Not classified





## 1 L Black Ink type JP-K72

<u>Serious eye damage/irritation</u>	- Eye irritation - Category 2 - Causes serious eye irritation
	- Irritating to eyes.
<u>Respiratory or skin sensitisation</u>	- Skin sensitization - Category 1 - May cause an allergic skin reaction
<u>Germ cell mutagenicity</u>	- Not classified
<u>Carcinogenicity</u>	- Not classified
<u>Reproductive toxicity</u>	- Not classified
<u>Specific target organ toxicity - Single exposure</u>	- Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation - May cause drowsiness or dizziness
<u>Specific target organ toxicity - Repeated exposure</u>	- Not classified
<u>Aspiration hazard</u>	- Not classified

### SECTION 12 - Ecological information

#### 12.1. - Toxicity

##### Toxicity values of mixture

EC50 48 hr crustacea	70600 mg/l
LC50 96 hr fish	No data available
ErC50 algae	No data available
ErC50 other aquatic plants	No data available
NOEC chronic fish	No data available
NOEC chronic crustacea	No data available
NOEC chronic algae	No data available
NOEC chronic other aquatic plants	No data available

- The substance/mixture does not fulfill the criteria of the acute aquatic toxicity according to Regulation (EC) No 1272/2008 [CLP], Annex I.

#### 12.2. - Persistence and degradability

Biochemical oxygen demand (BOD)	No data available
Chemical oxygen demand (COD)	No data available
% of biodegradation in 28 days	No data available

- No information available.



---

## 1 L Black Ink type JP-K72

---

### 12.3. - Bioaccumulative potential

Bioconcentration factor (BCF)	No data available
Log Kow - Partition coefficient: n-octanol/water	No data available

- No indication of bioaccumulation potential.

### 12.4. - Mobility in soil

- No information available.

### 12.5. - Results of PBT and vPvB assessment

### 12.6. - Other adverse effects

- No information available.

---

## SECTION 13 - Disposal considerations

---

### 13.1. - Waste treatment methods

Appropriate methods of waste treatment - Dispose of waste according to applicable legislation.

Sewage disposal - No information available.

Special precautions for waste treatment - No information available.

Community or national or regional provisions - No information available.

---

## SECTION 14 - Transport information

---

### 14.1. - UN number

UN number (ADR) : UN1210

UN number (RID) : UN1210

UN number (ADN) : UN1210

UN number (IMDG) : UN1210

UN number (IATA) : UN1210

### 14.2. - UN proper shipping name



---

## 1 L Black Ink type JP-K72

---

<u>UN proper shipping name</u> (ADR)	: PRINTING INK, flammable or PRINTING INK RELATED MATERIAL (including printing ink thinning or reducing compound), flammable (vapour pressure at 50 °C not more than 110 kPa) 640D
<u>UN proper shipping name</u> (RID)	: PRINTING INK, flammable or PRINTING INK RELATED MATERIAL (including printing ink thinning or reducing compound), flammable (vapour pressure at 50 °C not more than 110 kPa) 640D
<u>UN proper shipping name</u> (ADN)	: PRINTING INK, flammable or PRINTING INK RELATED MATERIAL (including printing ink thinning or reducing compound), flammable (vapour pressure at 50 °C not more than 110 kPa) 640D
<u>UN proper shipping name</u> (IMDG)	: PRINTING INK, flammable or PRINTING INK RELATED MATERIAL (including printing ink thinning or reducing compound), flammable (vapour pressure at 50 °C not more than 110 kPa) 640D
<u>UN proper shipping name</u> (IATA)	: PRINTING INK, flammable or PRINTING INK RELATED MATERIAL (including printing ink thinning or reducing compound), flammable (vapour pressure at 50 °C not more than 110 kPa) 640D

14.3. - Transport hazard class(es)



## 1 L Black Ink type JP-K72

ADR Class : 3  
ADR Classification code : F1

Pictograms



Class (RID) : 3

Pictograms



Class (ADN) : 3

Pictograms



Class (IMDG) : 3

Pictograms



Class (IATA) : 3

Pictograms



### 14.4. - Packing group

Packing group : II

Packing group (RID) : II

Packing group (ADN) : II

Packing group (IMDG) : II

Packing group (IATA) : II

### 14.5. - Environmental hazards

Environmental hazards : No

Marine pollutant : No

### 14.6. - Special precautions for user



## 1 L Black Ink type JP-K72

### **ADR**

<u>ADR Classification code</u>	:	F1
<u>ADR Special provisions</u>	:	163+ 640D+367
<u>ADR Limited quantities</u>	:	5 L
<u>ADR Excepted quantities</u>	:	E2
<u>ADR Packing instructions</u>	:	P001 IBC02 R001
<u>ADR Special packing provisions</u>	:	PP1
<u>ADR Mixed packing provisions</u>	:	MP19
<u>Instructions for portable tanks and bulk containers</u>	:	T4
<u>Special provisions for portable tanks and bulk containers</u>	:	TP1 TP8
<u>ADR tank code</u>	:	LGBF
<u>ADR tanks special provisions</u>	:	
<u>Vehicle for tank carriage</u>	:	FL
<u>ADR Transport category</u>	:	2
<u>ADR Tunnel restriction code</u>	:	D/E
<u>ADR Special provisions loading, unloading and handling</u>	:	
<u>Special provisions - Packages</u> : <u>Special provisions - Bulk</u>	:	
<u>Special provisions - Operation</u>	:	S2, S20
<u>ADR Hazard Identification No.</u>	:	33

### **RID**

<u>Special provisions</u>	:	
<u>Limited quantities</u>	:	
<u>Excepted quantities</u>	:	

### **ADN**

<u>Special provisions</u>	:	
<u>Limited quantities</u>	:	
<u>Excepted quantities</u>	:	

### **IMDG**

<u>Special provisions</u>	:	
<u>Limited quantities</u>	:	5
<u>Excepted quantities</u>	:	E2
<u>Packing instructions</u>	:	P001
<u>Special packing provisions</u>	:	
<u>IBC instruction(s)</u>	:	
<u>IBC provisions</u>	:	
<u>Instructions for portable tanks and bulk containers</u>	:	
<u>Special provisions for portable tanks and bulk containers</u>	:	
<u>EmS codes</u>	:	
<u>Stowage and handling</u>	:	
<u>Segregation</u>	:	
<u>Properties and observations</u>	:	

### **IATA**



## 1 L Black Ink type JP-K72

PCA - Excepted quantities	:	E2
PCA - Limited Quantity - Packing Instructions	:	Y341
PCA - Limited Quantity - Maximum Net Quantity per Package	:	1
PCA - Packing Instructions	:	353
PCA - Maximum Net Quantity per Package	:	5
CAO - Packing Instructions	:	364
CAO - Maximum Net Quantity per Package	:	60
Special Provisions	:	
ERG Code	:	

14.7. - Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

### SECTION 15 - Regulatory information

15.1. - Safety, health and environmental regulations/legislation specific for the substance or mixture

Components in the list of None Reach candidates

Components in Annex XIV None

Components in Annex XVII None

VOC content No data available

15.2. - Chemical safety assessment

Chemical safety assessment carried out for the product - No information available.

### SECTION 16 - Other information

SDS versions

Version No.	Date of issue	Description of the amendments
1	26/01/2018	

Texts of the regulatory sentences

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Eye Irrit. 2	Eye irritation - Category 2
Eye Irrit. 2A	Eye irritation - Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
Skin Sens. 1	Skin sensitization - Category 1



---

## 1 L Black Ink type JP-K72

---

STOT SE 3 (H336)	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
---------------------	--

\*\*\* \*\*